

CORRO-SHIELD

Smooth, Repair & Caulk

The Corro-Shield line-up of smoothing, repair and caulking compounds consists of six unique products designed with Corro-Shield's traditional concern for quality and longevity. Whether you are preparing concrete floors and walls for finishing or caulking gaps and cracks, Corro-Shield products are unsurpassed in durability.

Floor Patching

CORRO-PATCH

- No Limit to Thickness
- Abrasion and Impact Resistant
- Same Thermal Expansion Properties as Concrete

CORRO-SCREED

- Use to Create Slope/Pitch
- Allows Feathering
- Fine Aggregate for "Tight" Finish

Wall & Ceiling Patching

CORRO POLY-GEL

- Dries Hard & Smooth
- Apply to Walls and Ceilings
- Fills Holes Up To 3" Without Sagging

CORRO ELAST-O-GEL

- Still Flexible After It Dries
- Expands & Contracts With Substrate
- Use Where Movement Is A Concern

Flexible Slab & Crack Patching

CORRO FLEXI-CAULK

- 100% Elongation
- Remains Flexible To -40°F/-40°C
- Designed for Expansion Joints

CORRO-LASTIC

- Pourable Formula of Flexi-Caulk
- Can be Reinforced With Fiberglass
- Resistant to Vibration & Slab Movement

CORRO-SHIELD

Smooth, Repair & Caulk

- ▶ **CORRO-PATCH**
- ▶ **CORRO-POLY-GEL**
- ▶ **CORRO FLEXI-CAULK**
- ▶ **CORRO-SCREED**
- ▶ **CORRO ELAST-O-GEL**
- ▶ **CORRO-LASTIC**

Floor Patching

Both **Corro-Patch** and **Corro-Screed** are 100% Solids Epoxy formulated for floors exposed to heavy traffic and intermittent chemicals. They meet ASTM C-884 giving them the same thermal expansion properties as concrete meaning they will not crack or come loose from the substrate.

Wall & Ceiling Patching

Corro Poly-Gel and **Corro Elast-O-Gel** are paste-like materials ideally formulated to fill voids, holes and cracks in both walls and ceilings. They are frequently used to produce a smooth surface over CMU and Block Walls making them sanitary and easy to clean.

Flexible Slab & Crack Patching

Corro Flexi-Caulk and **Corro-Lastic** are superior solutions to fill dynamic cracks, expansion joints and anywhere where two concrete slabs abut to one another. Their blend of Epoxy Resin and unique Urethane Polymer give them 100% elongation and aggressive adhesion to the concrete substrate.

Corro-Lastic is also used as a flexible membrane under most any polymer floor coating when slab movement is a possible concern.

Corro-Shield International Inc.
2575 United Lane
Elk Grove Village, IL. 60007 USA
1.800.298.7637

Corro-Shield Industries Inc.
4-115 First Street, Suite 532
Collingwood, ON, Canada L9Y 4W3
1.888.780.3229



www.corroshield.com

CORRO-SHIELD
SUPERIOR PERFORMANCE COATINGS